



Uygulama:

Deniz suyu, tatlı su, sintine, hava, gaz ve yakıt devreleri

Çalışma Basıncı: **maksimum 10 kgf/cm²**

Çalışma Sıcaklığı: -10 / +300 °C

Diğer Seçenekler:

Ayar Diskli, SDNR (F-7472)

Application:

Sea water, fresh water, waste water, air, gas and oil

Working pressure: **maximum 10 kgf/cm²**

Working temperature: -10 / +300 °C

Variants:

Regulating Disc, SDNR (F-7472)

BASINÇ VE SICAKLIK SAHALARI / PRESSURE AND TEMPERATURE RANGE

Steam of 205°C or less	Permissible Working Pressure Working Temperature		Hydraulic Test Pressure for Leak-Tightness of	
	Air, Gas, Oil & Pulsation Water	Non-Shock Water of 120°C or less	Casing (Body)	Closure (Seat)
12 kgf/cm ²	12 kgf/cm ²	14 kgf/cm ²	21 kgf/cm ²	15,4 kgf/cm ²

PARÇA LİSTESİ / PART LIST

No	Parça Açıklaması Part Desc.	Materyal Material	No	Parça Açıklaması Part Desc.	Materyal Material
1	Gövde / Body	Cast Steel	6	Volan / Handwheel	GG 25
2	Kapak / Bonnet	Cast Steel	7	Salmastra / Gland Packing	Graphite
3	Burç / Seat Ring	RG 5	8	Salmastra Baskısı / Gland	RG 5
4	Disk / Disc	RG 5	9	Kapak Contası / Gasket	Graphite
5	Mil / Stem	Special Brass	10	Civata – Somun / Bolt – Nut	Brass/Steel

ÖLÇÜLER / DIMENSIONS

IMPA STOP	IMPA SDNR	DN	Face to Face	Flange Dia.	Flange Bolt Hole Pitch	Flange Bolt Hole Number	Flange Bolt Hole Hole	Weight KG
750421	751216	50	120	155	120	4	19	16,3
750422	751217	65	130	175	140	4	19	23
750423	751218	80	140	185	150	8	19	25,3
750424	751219	100	160	210	175	8	19	37
750425	751220	125	180	250	210	8	23	57,1
750426	751221	150	205	280	240	8	23	77,2
750427	751222	200	230	330	290	12	23	116
750428	-	250	290	400	355	12	25	188
750429	-	300	320	445	400	16	25	256