



Uygulama:

Sıcak ve soğuk su sistemleri, asit ve alkali özelliği bulunmayan sıvı akışkanlar için sürgülü valf
Çalışma Basıncı: **maksimum 10 bar**
Çalışma Sıcaklığı: -10 / +205 °C

Application:

Gate valve for hot and cold water, non-acidic and non-flammable liquid fluids
Working pressure: **maximum 10 bars**
Working temperature: -10 / +205°C

Diğer Seçenekler:

İndikatör, Tahliye Tapası, Dişli Kutusu, Elektrik Aktüatörü

Variants:

Indicator, Drain Plug, Gearbox, Electric Actuator

BASINÇ VE SICAKLIK SAHALARI / PRESSURE AND TEMPERATURE RANGE

Permissible Working Pressure Working Temperature			Hydraulic Test Pressure for Leak-Tightness of	
Steam of 200°C or less	Air, Gas, Oil & Pulsation Water	Non-Shock Water of 120°C or less	Casing (Body)	Closure (Seat)
8 kgf/cm ²	10 kgf/cm ²	14 kgf/cm ²	21 kgf/cm ²	15,4 kgf/cm ²

PARÇA LİSTESİ / PART LIST

No	Parça Açıklaması Part Desc.	Materyal Material	No	Parça Açıklaması Part Desc.	Materyal Material
1	Gövde / Body	Cast Iron	6	Volan / Handwheel	Cast Iron
2	Kapak / Bonnet	Cast Iron	7	Salmastra / Gland Packing	Graphite
3	Sürgülü Burcu / Wedge Ring	Bronze	8	Salmastra Bileziği / Gland	Bronze
4	Disk / Disc	Special Brass	9	Conta / Gasket	Graphite
5	Mil / Stem	Special Brass			

ÖLÇÜLER / DIMENSIONS

IMPA	DN	Face to Face	Flange Dia.	Flange Bolt Hole Pitch	Number	Hole	Weight KG
750821	50	200	155	120	4	19	19,4
750822	65	220	175	140	4	19	27,6
750823	80	230	185	150	8	19	33
750824	100	250	210	175	8	19	45,8
750825	125	270	250	210	8	23	65,9
750826	150	290	280	240	8	23	86
750827	200	320	330	290	12	23	136
750828	250	380	400	355	12	25	230
750829	300	440	440	400	16	25	331