



Uygulama:

Deniz suyu, tatlı su, sintine, hava, gaz ve yakıt devreleri

Çalışma Basıncı: **maksimum 20 kgf/cm²**

Çalışma Sıcaklığı: -10 / +400°C

Diğer Seçenekler:

Ayar Diskli, SDNR (F-7474)

Application:

Sea water, fresh water, waste water, air, gas and oil

Working pressure: **maximum 20 kgf/cm²**

Working temperature: -10 / +400°C

Variants:

Regulating Disc, SDNR (F-7474)

BASINÇ VE SICAKLIK SAHALARI / PRESSURE AND TEMPERATURE RANGE

Steam of 205°C or less	Permissible Working Pressure Working Temperature		Hydraulic Test Pressure for Leak-Tightness of	
	Air, Gas, Oil & Pulsation Water	Non-Shock Water of 120°C or less	Casing (Body)	Closure (Seat)
31 kgf/cm ²	31 kgf/cm ²	34 kgf/cm ²	51 kgf/cm ²	37,4 kgf/cm ²

PARÇA LİSTESİ / PART LIST

No	Parça Açıklaması Part Desc.	Materyal Material	No	Parça Açıklaması Part Desc.	Materyal Material
1	Gövde / Body	Cast Steel	6	Volan / Handwheel	GG 25
2	Kapak / Bonnet	Cast Steel	7	Salmastra / Gland Packing	Graphite
3	Burç / Seat Ring	RG 5	8	Salmastra Baskısı / Gland	RG 5
4	Disk / Disc	RG 5	9	Kapak Contası / Gasket	Graphite
5	Mil / Stem	Special Brass	10	Civata – Somun / Bolt – Nut	Brass/Steel

ÖLÇÜLER / DIMENSIONS

IMPA STOP	IMPA SDNR	DN	Face to Face	Flange Dia.	Flange Bolt Hole		Weight
					Pitch	Number	Hole
750441	751246	32	100	135	100	4	19
750442	751247	40	110	140	105	4	19
750443	751248	50	125	155	120	8	19
750444	751249	65	135	175	140	8	19
750445	751250	80	150	200	160	8	23
750446	751251	100	170	225	185	8	23
750447	751252	125	200	270	225	8	25
750448	751253	150	225	305	260	12	25
750449	751254	200	280	350	305	12	25
750450	751255	250	310	430	380	12	27