



Uygulama:

Sıcak ve soğuk su sistemleri, asit ve alkali özelliği bulunmayan sıvı akışkanlar için sürğülü valf
Çalışma Basıncı: **maksimum 5 bar**
Çalışma Sıcaklığı: -10 / +205 °C

Diğer Seçenekler:

İndikatör, Tahliye Tapası, Dişli Kutusu, Elektrik Aktüatörü



Application:

Gate valve for hot and cold water, non-acidic and non-flammable liquid fluids
Working pressure: **maximum 5 bars**
Working temperature: -10 / +205°C

Variants:

Indicator, Drain Plug, Gearbox, Electric Actuator

BASINÇ VE SICAKLIK SAHALARI / PRESSURE AND TEMPERATURE RANGE

Permissible Working Pressure Working Temperature			Hydraulic Test Pressure for Leak-Tightness of	
Steam of 200°C or less	Air, Gas, Oil & Pulsation Water	Non-Shock Water of 120°C or less	Casing (Body)	Closure (Seat)
5 kgf/cm ²	5 kgf/cm ²	7 kgf/cm ²	10,5 kgf/cm ²	7,7 kgf/cm ²

PARÇA LİSTESİ / PART LIST

No	Parça Açıklaması Part Desc.	Materyal Material	No	Parça Açıklaması Part Desc.	Materyal Material
1	Gövde / Body	Cast Iron	6	Volan / Handwheel	Cast Iron
2	Kapak / Bonnet	Cast Iron	7	Salmastra / Gland Packing	Graphite
3	Sürğü Burcu / Wedge Ring	Bronze	8	Salmastra Bileziği / Gland	Bronze
4	Disk / Disc	Special Brass	9	Conta / Gasket	Graphite
5	Mil / Stem	Special Brass			

ÖLÇÜLER / DIMENSIONS

IMPA	DN	Face to Face	Flange Dia.	Pitch	Flange Bolt Hole Number	Hole	Weight KG
780801	50	180	130	105	4	15	13,5
750802	65	190	165	130	4	15	19
750803	80	200	180	145	4	19	24,5
750804	100	230	200	165	8	19	35,3
750805	125	250	235	200	8	19	48,1
750806	150	270	265	230	8	19	65,3
750807	200	290	320	280	8	23	103
750808	250	330	385	345	12	23	164
750809	300	370	430	390	12	23	236